

Sensor-switched LED outdoor light

L 930 LED

Anthracite

EAN 4007841 067199

Article number 067199



LED

30 years (Ø 4,5h / day)

3000 K

3000K warm-white



infrared sensor 140°



max. 12 m



IP44



2/20 lux



2/15 min



manual override 4h



energy saving

3 years

manufacturer's warranty steinel.de/garantie

Function description

Magic lighting with aesthetic appeal. The 9 W sensor-switched outdoor light comes as an up/downlight in a classy aluminium look, and bathes building walls in warm white light (3000 K). The 140° IR sensor has a reach of 12 m. Added to this is the soft light start function and up to 4 h manual override for continuous light. Interconnectable by cable. Colour: anthracite. Ideal mounting height: 2 m.

L 930 LED

Anthracite

EAN 4007841 067199

Article number 067199

Technical specifications

Dimensions (L x W x H)	92 x 63 x 137 mm	Mechanical scalability	No
Mains power supply	220 – 240 V / 50 – 60 Hz	Reach, radial	r = 2 m (5 m ²) / r = 4 m (20 m ²)
Mounting height max.	2,50 m	Reach, tangential	r = 5 m (31 m ²) / r = 12 m (176 m ²)
Sensor Technology	passive infrared	Photo-cell controller	Yes
Output	9 W	Twilight setting	2 – 20 lx
Interconnection	Yes	Time setting	120 s – 15 Min.
Type of interconnection	Master/master	Basic light level function	Yes
Interconnection, number	10 lights max.	Basic light level function, detail	LED effect light
Slave modeselectable	No	Basic light level function time	all/half night
Luminous flux	603 lm	Main light adjustable	No
Efficiency	67 lm/W	Functions	Motions sensor, Light sensor, Normal / test mode, Orientation light
Colour temperature	3000 K	Soft light start	Yes
Colour variation LED	SDCM3	Continuous light	selectable, 4h
Colour Rendering Index	80-89	Impact resistance	IK03
With lamp	Yes, STEINEL LED system	IP-rating	IP44
Lamp	LED cannot be replaced	Protection class	I
LED life expectancy (max. °C)	50000 h	Ambient temperature	-20 – 40 °C
Drop in luminous flux in accordance with LM80	L70B10	Housing material	Aluminium
Base	without	Cover material	Plastic, opal
LED cooling system	Passive Thermo Control	Manufacturer's Warranty	3 years
With motion detector	Yes	includes sheet of self-adhesive numbers	No
Detection angle	140 °	Settings via	DIP switches
Sneak-by guard	No	With remote control	No
Capability of masking out individual segments	No	Version	Anthracite
Electronic scalability	Yes	PU1, EAN	4007841067199

Sensor-switched LED outdoor light

L 930 LED


Anthracite

EAN 4007841 067199

Article number 067199



Detection Zone




Mögliche Montagehöhe: 1,80 m – 2,50 m


Orange: radial

Schwarz: tangential

Dimension Drawing



Circuit diagram



Master/master interconnection circuit diagram

